

## Cisco 5x20U Broadband Processing Engine for the Cisco uBR10012 Universal Broadband Router

The Cisco® 5x20U Broadband Processing Engine (BPE) for the Cisco uBR10012 Universal Broadband Router combines industry-leading port density, an advanced RF feature set, next-generation advanced time division multiple access (A-TDMA) capabilities, and Data Over Cable Service Interface Specifications (DOCSIS) and European DOCSIS (EuroDOCSIS) support—on a single line card (Figure 1). The line card also supports an extended DOCSIS upstream frequency range of 5 to 55 MHz and downstream support of 70 to 860 MHz for DOCSIS operations in Japan.

The Cisco 5x20U BPE addresses the expanding service and operational needs of multiple system operators (MSOs). An unmatched set of advanced features and a scalable architecture make the Cisco 5x20U BPE an ideal choice for cable operators facing the challenge of delivering carrier-class IP-based data, voice, and video services to a growing number of subscribers.

**Figure 1**  
Cisco 5x20U BPE



## Product Overview

The Cisco 5x20U BPE is a cable interface line card for the Cisco uBR10012 that performs cable modem termination system (CMTS) functions, such as:

- Physical layer (PHY) RF interface (upstream burst demodulation, downstream modulation, RF upconversion)
- Media Access Control (MAC) processing (modem registration, transmission opportunity scheduling, Layer 2 quality of service [QoS])
- On-board packet processing

Featuring a highly integrated and robust RF front end and the industry's most advanced processing engine for DOCSIS- and EuroDOCSIS-based networks, the Cisco 5x20U BPE enables high-performance, reliable, and secure bidirectional transmission of IP packets over the cable plant for data, voice, and video services. The card supports:

- DOCSIS: 6 MHz National Television Systems Committee (NTSC) channel operation, using standard (STD), Harmonic Related Carrier (HRC) or Incremental Related Carrier (IRC) frequency plans conforming to EIA-S542 and ITU J.83 Annex B. The card supports downstream channels in the 88 to 860 MHz range, and upstream channels in the 5 to 42 MHz range.
- EuroDOCSIS: 8 MHz Phase Alternating Line (PAL) and Systemme Electronique Couleur Avec Memoire (SECAM) channel plans conforming to the International Telecommunications Union (ITU) J.83 Annex A standard. The card supports a greater upstream spectrum range of 5 to 65 MHz and an increased downstream channel width of 8 MHz.
- DOCSIS with extensions for Japan: 6 MHz Annex B extension support with a downstream extended frequency range of 70 to 860 MHz and an upstream extended frequency range of 5 to 55 MHz.

Table 1 describes the product's features and benefits.

### Advanced RF Front End

The Cisco 5x20U BPE presents the industry's most advanced RF front-end design, combining the highest level of integration with enhanced RF robustness and performance. The innovative design, which uses leading PHY chips from multiple vendors, features five downstream modulators, five upconverters, and 20 upstream burst receivers on a single line card. It embeds the most advanced RF capabilities, such as direct sampling of the upstream channels and ingress noise cancellation and advanced equalization.

### Superior MAC

The Cisco 5x20U BPE features dedicated MAC layer hardware for maximum performance in large-scale deployments. The Cisco 5x20U BPE MAC layer hardware enables scalability to thousands of cable modems, simultaneously providing hardware acceleration for sophisticated security features, such as DOCSIS 1.1 extensions to baseline privacy interface (BPI). It also provides hardware acceleration for functions such as concatenation, fragmentation, and payload header suppression (PHS)—necessary to deploy advanced data and voice services.

**Table 1** Product Features and Benefits

Feature	Benefits
Industry-leading port density	<ul style="list-style-type: none"><li>• Reduces per-port cost</li><li>• Maximizes plant capacity (frequency reuse)</li></ul>
Advanced RF front end	<ul style="list-style-type: none"><li>• Optimizes RF performance and robustness</li></ul>
Integrated upconverter	<ul style="list-style-type: none"><li>• Reduces operational cost and complexity</li></ul>
Dense connector	<ul style="list-style-type: none"><li>• Reduces installation time</li><li>• Reduces mean time to repair (MTTR)</li></ul>
Onboard spectrum analyzer hardware	<ul style="list-style-type: none"><li>• Reduces return-path monitoring costs</li><li>• Enhances remote troubleshooting capabilities</li></ul>
Dedicated MAC layer hardware	<ul style="list-style-type: none"><li>• Provides hardware acceleration of DOCSIS 1.1 features</li><li>• Enables scalability of data and voice deployment</li><li>• Optimizes cable modem registration time</li><li>• Provides hardware-based Layer 2 QoS</li><li>• Allows use of best-of-breed PHY</li></ul>
DOCSIS, EuroDOCSIS, and extensions to support DOCSIS operations in Japan	<ul style="list-style-type: none"><li>• Provides operational savings</li><li>• Lowers capital expenditures (CapEx)</li><li>• Increases flexibility</li></ul>
DOCSIS and EuroDOCSIS 2.0 capable	<ul style="list-style-type: none"><li>• DOCSIS 1.x and 2.0 deployments</li><li>• Maximizes return on investment</li><li>• Provides advanced PHY robustness for DOCSIS 1.x and 2.0 deployments</li></ul>
Compatible with the Cisco uBR 3x10 RF Switch	<ul style="list-style-type: none"><li>• Preserves investment, independent of CMTS chassis or line card technology choice</li></ul>

## Specifications

Physical	<ul style="list-style-type: none"><li>• Occupies a single slot in the Cisco uBR10012 chassis</li><li>• Interface: Line card single mode, with intermediate reach connector</li><li>• Hot-swappable; no slot dependency</li><li>• Weight: 16 lbs (7.26 kg)</li><li>• Dimensions (H x W x D): 20 x 1.36 x 16 in. (50.80 x 3.55 x 10.64 cm)</li></ul>
Power	<ul style="list-style-type: none"><li>• Unit power: 185W</li></ul>
Reliability and Availability	<ul style="list-style-type: none"><li>• Mean time between failure (MTBF): 40,256 hours</li></ul>
Environmental	<ul style="list-style-type: none"><li>• Operating altitude: -197 to 13,123 ft (-60 to 4000 m)</li><li>• Storage temperature: -4 to 149°F (-20 to 65°C)</li><li>• Operating temperature, nominal: 41 to 104°F (5 to 40°C)</li><li>• Storage relative humidity: 5 to 95 percent</li><li>• Operating relative humidity: 10 to 90 percent</li></ul>
Regulatory Compliance	
Safety	<ul style="list-style-type: none"><li>• UL 1950, Third Edition (Safety of Information Technology Equipment, Including Electrical Business Equipment), with no D3 deviations</li><li>• CSA 950 1995 Third Edition (Safety of Information Equipment Technology, Including Electrical Business Equipment)</li><li>• EN 60950 (Safety of Information Equipment Technology, Including Electrical Business Equipment)</li><li>• IEC 60950</li><li>• ACA TS001, 1997 Test Report and Statement of Compliance AS/NZS3260</li></ul>
Electromagnetic Emissions	<ul style="list-style-type: none"><li>• EN55022: 1998 Class B</li><li>• CISPR 22: 1997 Class B</li><li>• CFR 47 Part 15 Class B</li><li>• ICES -003, Issue 2, Class B, April 1995</li><li>• VCCIV-3/2000.04</li><li>• AS/NZS 3548: 1995 Class B</li><li>• CNS-13438 Class B—BSMI (BCIQ) in Taiwan</li></ul>
Electromagnetic Immunity	<ul style="list-style-type: none"><li>• EN50082-1: 1992</li><li>• EN50082-1: 1997</li><li>• EN55024: 1998</li><li>• EN61000-3-2: 1995</li><li>• EN61000-3-3: 1995</li><li>• EN61000-4-2: 1995 [including AMD1 + AMD2] ESD immunity</li><li>• EN61000-4-3: 1997 Radiated RF field immunity</li><li>• EN61000-4-4: 1995 Immunity to electrical fast transients</li><li>• EN61000-4-5: 1995 Surge immunity</li><li>• EN61000-4-6: 1996 [including AMD1] RF conducted immunity</li></ul>

Network Equipment Building Systems (NEBS) - Level 3	<ul style="list-style-type: none"> <li>• Designed and tested to meet requirements of GR-1089-CORE - Issue 2, December 1997</li> <li>• Revision 1, February 1999</li> </ul>
Mechanical	<ul style="list-style-type: none"> <li>• IEC 68-2-1, IEC 68-2-2, IEC 68-2-56: Operational temperature and humidity</li> <li>• IEC 68-2-27: Operating shock</li> <li>• IEC 68-2-64, IEC 68-2-6, IEC 68-2-47: Operating and nonoperating vibration</li> <li>• IEC 68-2-32: Nonoperating freefall drop</li> <li>• IEC 68-2-40: Nonoperating altitude</li> <li>• IEC 68-2-27, IEC 68-2-32: Nonoperating mechanical shock</li> <li>• IEC 68-2-3: Nonoperating humidity</li> <li>• IEC 68-2-14, IEC 68-2-33: Nonoperating temperature shock</li> <li>• LEDs <ul style="list-style-type: none"> <li>– One power LED (green)</li> <li>– One status LED (green/yellow): solid green indicates the processor has booted and passed its diagnostics; LED blinks green on a protect card, yellow when in one of the booting states</li> <li>– Maintenance (yellow): indicates the line card can be removed</li> <li>– One upstream-enabled LED on each upstream port (green): upstream path is configured and able to pass traffic</li> <li>– One downstream-enabled LED on each downstream port (green): downstream path is configured and able to pass traffic through the upconverter at the radio frequencies</li> </ul> </li> </ul>
Network Management	
Standard Management Information Bases (MIBs)	<ul style="list-style-type: none"> <li>• IF-MIB (RFC-2233)</li> <li>• ENTITY-MIB (RFC-2737)</li> <li>• MIBII (RFC1213)</li> <li>• EtherLike-MIB (RFC-2665)</li> <li>• IGMP-MIB (RFC-2993)</li> <li>• RMON-MIB (RFC-1757)</li> </ul>
Expression MIBs	<ul style="list-style-type: none"> <li>• SNMPv2-SMI</li> <li>• SNMPv2-TC</li> <li>• SNMPv2-MIB</li> <li>• IANAifType-MIB</li> </ul>
SNMPv3 MIBs	<ul style="list-style-type: none"> <li>• SNMP-FRAMEWORK-MIB (RFC-2571)</li> <li>• SNMP-MPD-MIB (RFC-2572)</li> <li>• SNMP-NOTIFICATION-MIB (RFC-2573)</li> <li>• SNMP-TARGET-MIB (RFC-2573)</li> <li>• SNMP-USM-MIB (RFC-2574)</li> <li>• SNMP-VACM-MIB (RFC-2575)</li> </ul>
DOCSIS and EuroDOCSIS MIB	<ul style="list-style-type: none"> <li>• DOCS-IF-MIB (v2 Rev04)</li> <li>• DOCS-CABLE-DEVICE-MIB (RFC-2669)</li> <li>• DOCS-BPI-PLUS-MIB (Rev 5)</li> <li>• DOCS-QOS-MIB (Rev 4)</li> <li>• DOCS-CABLE-DEVICE-TRAP-MIB</li> <li>• DOCS-SUBMGT-MIB (Rev 2)</li> </ul>

Cisco DOCSIS MIBs	<ul style="list-style-type: none"> <li>• CISCO-DOCS-EXT-MIB</li> <li>• CISCO-DOCS-REMOTE-QUERY-MIB</li> <li>• CISCO-DOCS-QOS-EXT-MIB</li> <li>• CISCO-CABLE-SPECTRUM-MIB</li> <li>• CISCO-CABLE-AVAILABILITY-MIB</li> <li>• CISCO-DOCS-EXT-CAPABILITY-MIB</li> </ul>
Cisco Generic MIBs	<ul style="list-style-type: none"> <li>• CISCO-SYSLOG-MIB</li> <li>• CISCO-SMI-MIB</li> <li>• CISCO-TC-MIB</li> <li>• CISCO-PRODUCTS-MIB</li> <li>• CISCO-FLASH-MIB</li> <li>• CISCO-CONFIG-MAN-MIB</li> <li>• CISCO-CONFIG-COPY-MIB</li> <li>• CISCO-MEMORY-POOL-MIB</li> <li>• CISCO-BULK-FILE-MIB</li> <li>• CISCO-SONET-MIB</li> <li>• CISCO-TCP-MIB</li> <li>• CISCO-RTTMON-MIB</li> <li>• CISCO-FTP-CLENT-MIB</li> <li>• CISCO-IPMROUTE-MIB</li> <li>• CISCO-QUEUE-MIB</li> <li>• CISCO-IMAGE-MIB</li> <li>• CISCO-ENVMON-MIB</li> <li>• CISCO-ENTITY-VENDORTYPE-OID-MIB</li> <li>• CISCO-PRODUCTS-MIB</li> </ul>

## Ordering Information

### Part Number and Product Description

#### UBR10-5X20U-D

New Cisco uBR10012 BPE, 5 downstream w/upx, 20 upstream, spectrum analyzer, dense connector

The dense connector is designed to simplify installation and maximize serviceability. Please make sure you procure a correctly terminated cable to connect to this connector by ordering one of the cable kits from Cisco, or by purchasing an equivalent set from White Sands Engineering.

<http://www.whitesandsengineering.com>

**Table 2** Cable Kits Part Numbers and Descriptions

	Cisco Cable Kit	White Sands
UBR10-5X20U-D	CAB-RFSW520TIMM cable bundle, 5x20-Dense to RF switch, 1 m, term CAB-RFSW520TPMF cable bundle, 5x20-Dense to MSO plant, 3 m	2x WS943 (10-pack) and 1x WS942 (5-pack) Mini RG59 95% TC Braid 100% foil shield

**Corporate Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA

[www.cisco.com](http://www.cisco.com)

Tel: 408 526-4000

800 553-NETS (6387)

Fax: 408 526-4100

**European Headquarters**

Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands

[www-europe.cisco.com](http://www-europe.cisco.com)

Tel: 31 0 20 357 1000

Fax: 31 0 20 357 1100

**Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA

[www.cisco.com](http://www.cisco.com)

Tel: 408 526-7660

Fax: 408 527-0883

**Asia Pacific Headquarters**

Cisco Systems, Inc.  
Capital Tower  
168 Robinson Road  
#22-01 to #29-01  
Singapore 068912

[www.cisco.com](http://www.cisco.com)

Tel: +65 6317 7777

Fax: +65 6317 7799

**Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the**

**Cisco Web site at [www.cisco.com/go/offices](http://www.cisco.com/go/offices)**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

All contents are Copyright © 1992–2003 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco Arrow logo, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratm, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0304R)  
RDA4662 04/03